

→ Direct flow reverse osmosis

RO PURECLEER COMPACT HL SERIES

SPECIFICATIONS

EQUIPMENT MODEL	COMPACT HL 400 239508	COMPACT HL 600 239509	COMPACT HL 800 239510	COMPACT HL 1000 239511	COMPACT HL 1200 239512
Max. inlet water salinity	3500 ppm	3500 ppm	3500 ppm	3500 ppm	3500 ppm
Production capacity (L/24h)	9600	14400	19200	24000	28800
Production capacity (L/hour)	400	600	800	1000	1200
No. of membranes	x2	x3	x4	x5	x6
Membrane model	4040				
Salt rejection	99%				
Recovery percentage	Adjustable up to 75%				
Max. working pressure	19 Kg/cm ²				
Min. dynamic inlet pressure	2 Kg/cm ²				
Inlet water temperature (min - max.)	3°C / 35°C				
Inlet pH	3 - 11 pH				
Maximum inlet chlorine level	<0,1 ppm				
Installed power	2,2 Kw				
Power supply	III 380 V - 50 H _z				
Electronic control*	Yes				
Inlet connection	1" BSP female thread				
Product connection	1/2" BSP	1/2" BSP	1/2" BSP	1/2" BSP	1" BSP
Reject connection	1/2" BSP	1/2" BSP	1/2" BSP	1/2" BSP	1" BSP
Dimensions**	1682 x 640 x 634 mm				



CODE ORIGINAL SUPPLIES

239504

RO IND. Purecleer mixing kit

* On the pressure pump.
** Height x width x depth.



Kinetico Spain S.L.U (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 for Kinetico Spain S.L.U (B-60326279).



Kinetico Spain S.L.U (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



Kinetico Spain S.L.U (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOP18000008U6 and 13/02/2018 as a date of entry of the authorization.