

→ Direct flow reverse osmosis

RO PURECLEER COMPACT L SERIES

SPECIFICATIONS

EQUIPMENT MODEL	COMPACT L 380 239505	COMPACT L 160 239506	COMPACT L 1150 239507
Max. inlet water salinity	6000 ppm		
Production capacity (L/24h)	9120	18240	27600
Production capacity (L/hour)	380	760	1150
No. of membranes	x2	x4	x6
Membrane model	4040		
Salt rejection	99%		
Recovery percentage	Adjustable up to 75%		
Max. working pressure	19 Kg/cm ²		
Min. dynamic inlet pressure	2 Kg/cm ²		
Inlet water temperature (min - max.)	3°C / 35°C		
Inlet pH	3 - 11 pH		
Maximum inlet chlorine level	<0,1 ppm		
Installed power	2,2 Kw		
Power supply (50 Hz single-phase)	III 380V 50 H ₃		
Electronic control*	Yes		
Inlet connection	1" BSP female thread		
Product connection	1/2" BSP	1/2" BSP	1" BSP
Reject connection	1/2" BSP	1/2" BSP	1" BSP
Dimensions**	1682 x 640 x 634 mm		



CODE ORIGINAL SUPPLIES

239504

RO IND. Purecleer mixing kit

* On the pressure pump.

** Height x width x depth.



Kinetico Spain S.L.U (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 for Kinetico Spain S.L.U (B-60326279).



Kinetico Spain S.L.U (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



Kinetico Spain S.L.U (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOP18000008U6 and 13/02/2018 as a date of entry of the authorization.