

→ Direct flow reverse osmosis

RO PURECLEER SLIM HL SERIES

SPECIFICATIONS

EQUIPMENT MODEL	SLIM HL 200 239513	SLIM HL 400 239514
Max. inlet water salinity	3500 ppm	3500 ppm
Production capacity (L/24h)	4800	9600
Production capacity (L/hour)	200	400
No. of membranes	x1	x2
Membrane model	4040	
Salt rejection	99%	
Max. working pressure	19 Kg/cm ²	
Min. dynamic inlet pressure	1 Kg/cm ²	
Inlet water temperature (min - max.)	3°C / 35°C	
Inlet pH	3 - 11	
Maximum inlet chlorine level	<0,1 ppm	
Installed power	1,5 kW	
Power supply	II 220 V 50 H ₃	
Electronic control*	NO	
Inlet connection	1" BSP female thread	
Product connection	1/2" BSP	
Reject connection	1/2" BSP	
Dimensions**	1619 x 706 x 465 mm	

CODE

ORIGINAL SUPPLIES

239504

RO IND. Purecleer mixing kit



- * On the pressure pump.
** Height x width x depth.



MEMBER
Water Quality
ASSOCIATION

Kinetico Spain S.L.U (B-60326279), is member of the Water Quality Association.



ACREDITED BY ENAC
Certif. nº 34/5200/14/0712

The trading of water treatment and household appliances as well as designing and teaching of non-official training courses related with its technology are certified and comply with the UNE-ISO-9001 for Kinetico Spain S.L.U (B-60326279).



Kinetico Spain S.L.U (B-60326279) is an Aqua España member, who belongs Aqua Europa (Federation of European nation associations).



Kinetico Spain S.L.U (B-60326279), has the rights granted for Authorized Economic Operator with number ESAEOF18000008U6 and 13/02/2018 as a date of entry of the authorization.